

Countermeasure				Preventable Crash Count (per HSIP)						
WC	Improvement	CRF	CMF	K	A	B	C	O	U	TOTAL
110	Install Pedestrian Signal	0.34	0.66	0	3	0	1	0	0	4
108	Improve Traffic Signal	0.24	0.76	1	4	22	284	50	0	361
203	Install Raised Median	0.25	0.75	2	2	60	801	115	0	980
204	Flatten Side Slope	0.05	0.95	1	0	1	2	0	0	4
209	Safety Treat Fixed Objects	0.5	0.5	1	0	4	21	4	3	33
304	Safety Lighting	0.49	0.51	1	3	16	181	26	3	230
401	Install Pavement Markings	0.2	0.8	1	7	65	885	129	1	1088
403	Install Pedestrian Crosswalk	0.1	0.9	0	5	3	2	2	0	12
407	Install Sidewalks	0.65	0.35	0	5	5	2	4	0	16
519	Add Left Turn Lane	0.25	0.75	1	1	18	255	44	0	319
520	Lengthen Left Turn Lane	0.4	0.6	0	0	8	148	27	0	183
521	Add Right Turn Lane	0.25	0.75	0	0	8	193	29	0	230

Preventable KA Crashes (KA*CRF)
1.0
1.2
1.0
0.1
0.5
2.0
1.6
0.5
3.3
0.5
0.0
0.0